

# Zato Cayman

## FCE40R KEY FEATURES

weight <i>without connection</i>	kg. 4.180	Lbs.9,215
opening	mm. 707	in. 28
depth	mm. 750	in. 30
reach <i>without connection</i>	mm. 3.370	in. 11' 06"
main body	fully enclosed • reinforced	
hydraulic rotation	360° continuous	
cylinder type	heavy duty • large bore • tempered rod • solid with main body • certified welding processes	
speed valve	integrated • spool type	
power increase	+ 20%	
production increase	+ 20%	
main pivot group	high strength steel • heavy duty	
end cap	wrapped, tempered	
slide puck system	single	
internal inspections access mode	recessed top cover plate	
cutting force at 345 bar / 5000 psi (main pin)	metric ton. 790	US ton. 871
cutting force at 350 bar / 5077 psi (main pin)	metric ton. 802	US ton. 884
cutting force at 380 bar / 5500 psi (main pin)	metric ton. 870	US ton. 959
excavator weight boom mounted (2 <sup>nd</sup> member)	ton. c/a * 24	Lbs. 53,000
excavator weight at stick mounted (3 <sup>rd</sup> member)	ton. c/a * 40	Lbs. 88,200

\*Excavator weight classes are indicative. Please always check your excavator lift capacities.

## BLADES

set of blades replacement time	30' c/a
upper/lower jaw blades (main blades / guide blade / razor blade)	4 way indexable • 4 cutting edges per blade
guide blades	double
cutting and moving jaw blades	all 4 equal • 2 + 2 pieces
piercing blades	bolt on

